

SAFETY DATA SHEET

Date Issued : 2/5/2007
MSDS No : PF608
Date Revised : 9/19/2014
Revision No : 4

Qualitek No Clean Paste Flux PF608

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Qualitek No Clean Paste Flux PF608

PRODUCT DESCRIPTION: No Clean Paste Flux

MANUFACTURER

Qualitek International, Inc.
 315 Fairbank St.
 Addison, IL 60101
Emergency Phone: (800) 535-5053
Service Number: (630) 628-8083

24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-535-5053 Infotrac
 1-352-323-3500 Outside the U.S.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Eye Irritation, Category 2

GHS LABEL



Exclamation
 mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H320: Causes eye irritation.

PRECAUTIONARY STATEMENT(S)

Prevention:

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P264: Wash hands thoroughly after handling.

Disposal:

P501: Dispose of contents/container in accordance to local/regional/national/international regulations.

POTENTIAL HEALTH EFFECTS

SAFETY DATA SHEET

Date Issued : 2/5/2007

MSDS No : PF608

Date Revised : 9/19/2014

Revision No : 4

Qualitek No Clean Paste Flux PF608

EYES: Fumes from this and other soldering products may cause eye irritation.

INGESTION: Ingestion of this or other soldering products may cause headache, nausea, and muscular pain.

INHALATION: Inhalation of the fumes from this or other soldering products may cause headache, nausea and muscular pain.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Modified Rosin	< 56	65997-05-9
Glycol Ether Solvent	< 25	112-59-4
Ethoxylated Oleyl Alcohol	< 13	9004-98-2
Polyamide	< 6	25038-54-4

4. FIRST AID MEASURES

EYES: MOLTEN PRODUCT: Cool burns with plenty of low-pressure water. Get immediate medical attention.

SOLID PRODUCT: Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Get medical attention if irritation develops.

SKIN: MOLTEN PRODUCT: Immediately cool skin burns with water and cold packs for at least 15 minutes. Do not put ice directly on the skin. Do not attempt to remove solidified product from the skin, as damage may result. Get immediate medical attention. **SOLID PRODUCT:** Immediately wash skin with soap and copious amounts of water. Use lotion to prevent dryness. Get medical attention if irritation develops.

INGESTION: If victim is conscious, give several glasses of water and keep the airway clean. Get medical attention.

INHALATION: Move person to fresh air. If breathing is stopped or is labored, give assisted respiration (e.g. mouth-to-mouth). Supplemental oxygen may be used. Get medical attention.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

CHRONIC EFFECTS: Prolonged or repeated exposure due to ingestion may cause anemia, insomnia, weakness, constipation and abdominal pain. Prolonged or repeated exposure due to skin exposure and inhalation may cause skin rash and damage to the mucous membranes.

COMMENTS: If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this MSDS to the physician/health care professional.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Carbon dioxide, dry chemical or appropriate foam. Water may be effective for cooling containers but not for extinguishing.

EXPLOSION HAZARDS: Closed containers may explode when exposed to fire conditions.

SAFETY DATA SHEET

Date Issued : 2/5/2007
MSDS No : PF608
Date Revised : 9/19/2014
Revision No : 4

Qualitek No Clean Paste Flux PF608

FIRE FIGHTING EQUIPMENT: Self contained breathing apparatus and full protective turn-out gear.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Scoop up material and deposit in appropriate containers. Clean up residual spill area with isopropanol or detergent water.

7. HANDLING AND STORAGE

GENERAL PROCEDURES: Store in a cool dry place away from incompatible materials. Keep away from heat, flame, sparks and other sources of ignition. Keep containers closed when not in use.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: Local exhaust may be necessary if working with the product in enclosed areas or at elevated temperatures.

PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Face shield, safety glasses with side shield or chemical splash goggles.

SKIN: Rubber, chemical resistant gloves. When material is heated, wear gloves to protect against thermal burns.

RESPIRATORY: Not normally needed in well ventilated areas. If the ventilation is insufficient to remove smoke from soldering processes, use NIOSH/MSHA approved cartridge type respirator.

PROTECTIVE CLOTHING: Protective clothing and safety shoes as necessary to minimize contact.

WORK HYGIENIC PRACTICES: Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

OTHER USE PRECAUTIONS: Eye wash station and quick drench safety shower in immediate work area.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Mild.

APPEARANCE: Smooth amber paste.

FLASH POINT AND METHOD: > 116°C (240°F)

FLAMMABLE LIMITS: N/E

AUTOIGNITION TEMPERATURE: > 227°C (440°F)

VAPOR PRESSURE: Not Determined

VAPOR DENSITY: Not Determined

BOILING POINT: 256°C (493°F) @ 760 mmHg

MELTING POINT: > 100°C (212°F)

SOLUBILITY IN WATER: Partially Soluble

SAFETY DATA SHEET

Date Issued : 2/5/2007
 MSDS No : PF608
 Date Revised : 9/19/2014
 Revision No : 4

Qualitek No Clean Paste Flux PF608

10. STABILITY AND REACTIVITY

STABILITY: Stable.

POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Under fire conditions carbon dioxide and carbon monoxide may be evolved.

INCOMPATIBLE MATERIALS: Strong acids and strong oxidizers should be avoided..

11. TOXICOLOGICAL INFORMATION

CARCINOGENICITY

IARC: Not listed.

NTP: Not listed.

OSHA: Not listed.

12. ECOLOGICAL INFORMATION

GENERAL COMMENTS: No information on ecological toxicity or biodegradability is available at this time.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not regulated by DOT

CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: Not regulated

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HAZARD CATEGORIES: Not considered a hazard.

313 REPORTABLE INGREDIENTS: None.

TSCA (TOXIC SUBSTANCE CONTROL ACT)

TSCA STATUS: All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances

SAFETY DATA SHEET

Date Issued : 2/5/2007
MSDS No : PF608
Date Revised : 9/19/2014
Revision No : 4

Qualitek No Clean Paste Flux PF608

Control Act (TSCA) Chemical Substance Inventory.

CALIFORNIA PROPOSITION 65: When used for soldering and similar applications chemicals may be produced which are known to some states to cause birth defects or other reproductive harm.

16. OTHER INFORMATION

REASON FOR ISSUE: New format

APPROVED BY: P. Han **TITLE:** Technical Director

PREPARED BY: J. Saleda-Layton

INFORMATION CONTACT: (630) 628-8083

REVISION SUMMARY: This MSDS replaces the 12/10/2013 MSDS. Revised: **Section 2:** .

HMIS RATING

HEALTH	<input type="checkbox"/>	2
FLAMMABILITY	<input type="checkbox"/>	1
PHYSICAL HAZARD	<input type="checkbox"/>	0
PERSONAL PROTECTION	<input type="checkbox"/>	B

MANUFACTURER DISCLAIMER: The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Material Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Material Safety Data Sheets as a source of hazards information and response.