

QUALITEK[®]

Ceasolder-PAL (Pink Acrylic Latex) Peelable Solder Mask

DESCRIPTION

Ceasolder- PAL is a temporary, peelable solder mask comprised of a thixotropic, synthetic acrylic latex designed to withstand fluxing, wave soldering and cleaning operations. Unlike natural latex mask, it contains no offensive ammonia and hence is non-corrosive to copper, gold, silver or presoldered surfaces. In addition, stability problems are averted. May be used in applications such as robotic, pneumatic, hand applied or template screening.

BENEFITS

- Easily peeled
- Acrylic Latex
- Non-flammable
- Ammonia-Free

APPLICATION

Apply Ceasolder-PAL by brush coating or through squeeze bottle (Suggested coating thickness should be 20-30mils). If material begins to thicken, use DI water to reduce viscosity. Surface should be clean and dry before applying Ceasolder-PAL.

Cure Time

1 Hr Ambient 30 min. @ 65 °C 20 Min @ 82 °C

PHYSICAL & CHEMICAL CHARACTERISTICS

| Color and Appearance | Pink |
|---|--------------------|
| pH 5% soln | 7.0 - 9.0 |
| Solids | $66 \pm 1\%$ |
| Specific Gravity @24 ^o C | 1.02 |
| Viscosity | |
| Brookfield ¹ | 60,000 – 70,000cps |
| Flash Point | None |
| Shelf life (un-opened) | 1 year from (DOM) |
| Storage Temperature | 22-23°C |
| 1. Brookfield RVF, spindle, #5, 25 ^o C, 20 RPM | |

PACKAGING & STORAGE

Ceasolder-PAL is available in 8 ounce squeeze bottles, and 1gallon containers. Recommended storage temperature is $65^{\circ} - 75^{\circ}$ F. Keep containers tightly sealed and out of direct sunlight.

Qualitek ® is a trademark of Qualitek International, Inc.

TEL: (630) 628-8083 FAX: (630) 628-6543 E-MAIL: solder@qualitek.com HOME PAGE:http://www.qualitek.com HEADQUARTERS: 315 Fairbank St., Addison, IL 60101 U.S.A. - Santa Clara, CA – Singapore WORLDWIDE BRANCHES: UNITED KINGDOM – MEXICO – CHINA – PHILIPPINES - SINGAPORE QUALITEK_INTERNATIONAL, INC. AN ISO 9002 CERTIFIED COMPANY

This data is based on information that the manufacturer believed to be reliable and offered in good faith. Qualitek International, Inc. makes no warranties expressed or implied as to its accuracy and assumes no responsibilities and liabilities arising out of its use by others as conditions and methods of use of the products is beyond the control of Qualitek International, Inc. The user must determine the suitability of the product before using it on a commercial basis. The warranties extend only to the conformity of the product to the physical descriptions. In no event will Qualitek International, Inc. be responsible for special, incidental and consequential damages whether the claim is in contract, negligence or otherwise.

Rev: 111210-Ceasolder-PAL

Consult MSDS for health and safety information