

Date Issued: 05/04/2007

SDS No: 2020

Date Revised: 11/24/2020

Revision No: 9

Qualitek® Water Soluble Wave Oil 2020

1. PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: Qualitek® Water Soluble Wave Oil 2020

PRODUCT DESCRIPTION: Water Soluble Wave Oil

MANUFACTURER

Qualitek International, Inc.

315 Fairbank St.

Addison, IL 60101

Emergency Phone: (800) 535-5053 **Customer Service:** (630) 628-8083

24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-535-5053 Infotrac

1-352-323-3500 Outside the U.S.

2. HAZARDS IDENTIFICATION

GHS CLASSIFICATIONS

Health:

Eye Irritation, Category 2A Skin Irritation, Category 3

GHS LABEL



Exclamation

mark

SIGNAL WORD: WARNING

HAZARD STATEMENTS

H320: Causes eye irritation.

H316: Causes mild skin irritation.

PRECAUTIONARY STATEMENT(S)

Prevention:

P280: Wear protective gloves/protective clothing/eye protection/face protection.

Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P302+P352: IF ON SKIN: Wash with plenty of water/...

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.



Date Issued: 05/04/2007

SDS No: 2020

Date Revised: 11/24/2020

Revision No: 9

Qualitek® Water Soluble Wave Oil 2020

Disposal:

P501: Dispose of contents/container in accordance to local/regional/national/international regulations.

POTENTIAL HEALTH EFFECTS

EYES: May cause irritation, experienced as mild discomfort and seen as a light excess redness of the eye(s).

SKIN: Brief contact may cause slight irritation. Prolonged contact as with clothing wetted with material, may cause more severe irritation and discomfort, seen as local redness and swelling.

INGESTION: May cause nausea, vomiting, and gastrointestinal irritation.

INHALATION: Vapors or mists in excess of permissible concentrations, or in unusually high concentrations generated from spraying, heating the material or as from exposure in poorly ventilated areas or confined spaces, may cause irritation of the nose and throat, headache, nausea and drowsiness.

MEDICAL CONDITIONS AGGRAVATED: There is no evidence that this product aggravates any existing medical conditions.

3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Non-ionic Surfactant	95	9016-45-9

4. FIRST AID MEASURES

INGESTION: If victim is conscious, give several glasses of water and keep the airway clean. Get medical attention.

INHALATION: Move person to fresh air. If breathing is stopped or is labored, give assisted respiration (e.g. mouth-to-mouth). Supplemental oxygen may be indicated. Seek medical advice if necessary.

SIGNS AND SYMPTOMS OF OVEREXPOSURE

CHRONIC EFFECTS: There are no known chronic effects associated with this material.

COMMENTS: If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this SDS to the physician/health care professional.

5. FIRE FIGHTING MEASURES

EXTINGUISHING MEDIA: Water spray, carbon dioxide, dry chemical or appropriate foam.

FIRE FIGHTING PROCEDURES: Water or foam may cause frothing, which can be violent and possibly endanger the life of the firefighter. Water may be used to keep fire-exposed containers cool until the fire is out.

6. ACCIDENTAL RELEASE MEASURES

GENERAL PROCEDURES: Avoid cotact with eyes and avoid breathing vapors. Transfer product to suitable, labeled containers for disposal at an approved facility. Absorb liquid spillage with inert materials such a sand, and wash the spill area with water and detergents.



Date Issued: 05/04/2007

SDS No: 2020

Date Revised: 11/24/2020

Revision No: 9

Qualitek® Water Soluble Wave Oil 2020

SPECIAL PROTECTIVE EQUIPMENT: Appropriate respiratory protection and protective clothing. Provide adequate ventlation during clean-up.

7. HANDLING AND STORAGE

HANDLING: Minimum feasible handling temperatures should be maintained.

STORAGE: Store in a cool, well ventilated place away from incompatible materials. Keep containers tightly closed when not in use. Protect containers from damage. Periods of exposure to high temperatures should be minimized and water contamination should be avoided.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

ENGINEERING CONTROLS: General (mechanical) room ventilation is expected to be satisfactory where this product is stored and handled and in closed equipment. Special local ventilation is needed at points where vapors can be expected to escape into the workplace air.

PERSONAL PROTECTIVE EQUIPMENT

SKIN: Rubber, chemical resistant gloves.

RESPIRATORY: Not normally needed in well ventilated areas. If vapor concentration is high, use NIOSH/MSHA approved respiratory protection device.

WORK HYGIENIC PRACTICES: Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

9. PHYSICAL AND CHEMICAL PROPERTIES

ODOR: Slight characteristic odor.

APPEARANCE: Pale liquid.

FLASH POINT AND METHOD: > 237°C (458.6°F) Cleveland Closed Cup

FLAMMABLE LIMITS: No data available VAPOR PRESSURE: No data available VAPOR DENSITY: No data available SPECIFIC GRAVITY: 1.024 to 1.074

10. STABILITY AND REACTIVITY

HAZARDOUS POLYMERIZATION: Will not occur under normal use and storage conditions.

STABILITY: Stable under ordinary use and storage conditions.

HAZARDOUS DECOMPOSITION PRODUCTS: Carbon dioxide, carbon monoxide, irritating aldehydes and ketones may be formed on burning. Heating in air may produce irritating aldehydes, acids, and ketones.

INCOMPATIBLE MATERIALS: None known.



Date Issued: 05/04/2007

SDS No: 2020

Date Revised: 11/24/2020

Revision No: 9

Qualitek® Water Soluble Wave Oil 2020

11. TOXICOLOGICAL INFORMATION

ACUTE TOXICITY

INHALATION LC₅₀: Believed to be practically nontoxic.

GENERAL COMMENTS: This product may contain residue (less than 100 ppm) concentration of ethylene oxide. Ethylene oxide causes tumors in laboratory animals.

12. ECOLOGICAL INFORMATION

ECOTOXICOLOGICAL INFORMATION: LC50 (96 Hour): Aquatic toxicity rating is believed to be > 1.00 - 10.00 ppm - moderately toxic.

13. DISPOSAL CONSIDERATIONS

DISPOSAL METHOD: Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

RCRA/EPA WASTE INFORMATION: This product is not a hazardous waste as listed in 40CFR261.33. It does not exhibit any of the hazardous characteristics listed in 40CFR261, Subpart C.

14. TRANSPORT INFORMATION

DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not regulated by DOT

NOTE: Not regulated by IATA and International Maritime Organization (IMO)

AIR (ICAO/IATA)

SHIPPING NAME: Not regulated by DOT

15. REGULATORY INFORMATION

UNITED STATES

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HEALTH HAZARDS: Immediate Hazard.

CERCLA (COMPREHENSIVE RESPONSE, COMPENSATION, AND LIABILITY ACT)

CERCLA RQ: Glycol Ethers (fraction of product matching EPA definition): 1.00 - 2.99 %, RQ: 1 lb Residual Ethylene Oxide CAS# 75-21-8: 0.001 %, RQ: 10.0 lbs

TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS
Non-ionic Surfactant	9016-45-9



Date Issued: 05/04/2007

SDS No: 2020

Date Revised: 11/24/2020

Revision No: 9

Qualitek® Water Soluble Wave Oil 2020

TSCA STATUS: All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

CALIFORNIA PROPOSITION 65: The following components are known to the State of California to cause cancer and/or reproductive toxicity and subject to warning and discharge requirements under the "Safe Drinking Water and Toxic Enforcement Act of 1986.": Ethylene Oxide (C, R) (trace amounts) C = Cancer Causing, R = Reproductive Toxicity

CANADA

WHMIS (WORKPLACE HAZARDOUS MATERIALS INFORMATION SYSTEM): Not regulated.

16. OTHER INFORMATION

REASON FOR ISSUE: New format

APPROVED BY: P. Han **TITLE:** Technical Director

PREPARED BY: J. Saleda-Layton Date Revised: 11/24/2020

INFORMATION CONTACT: (630) 628-8083

REVISION SUMMARY: This SDS replaces the 08/21/2017 SDS. Revised: Section 9: BOILING POINT, FLASH

POINT AND METHOD.