

# SAFETY DATA SHEET



**Date Issued :** 05/13/2022  
**SDS No :** 769LF  
**Date Revised :** 07/26/2022  
**Revision No :** 3

## Delta Lead Free Water Soluble Solder Paste Type 769LF

### 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Delta Lead Free Water Soluble Solder Paste Type 769LF

**PRODUCT DESCRIPTION:** Water Soluble Solder Paste

#### MANUFACTURER

Qualitek International, Inc.

315 Fairbank Street

Addison, IL 60101

**Emergency Phone:** (800)535-5053

**Customer Service:** (630)-628-8083

### 2. HAZARDS IDENTIFICATION

#### GHS LABEL



Exclamation  
mark



Health  
hazard

**SIGNAL WORD:** WARNING

#### HAZARD STATEMENTS

H351: Suspected of causing cancer (state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard).

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H335: May cause respiratory irritation.

#### PRECAUTIONARY STATEMENT(S)

##### Prevention:

P264: Wash hands thoroughly after handling.

P280: Wear protective gloves/protective clothing/eye protection/face protection.

##### Response:

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

P302+P352: IF ON SKIN: Wash with plenty of water/...

P301+P330+P331: IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

##### Storage:

# SAFETY DATA SHEET



Date Issued : 05/13/2022  
 SDS No : 769LF  
 Date Revised : 07/26/2022  
 Revision No : 3

## Delta Lead Free Water Soluble Solder Paste Type 769LF

P235: Keep cool.

### Disposal:

P501: Dispose of contents/container in accordance to local/regional/national/international regulations.

### POTENTIAL HEALTH EFFECTS

**EYES:** Fumes from this and other soldering products may cause eye irritation.

**SKIN:** Fumes from this and other soldering products may cause skin irritation.

**INGESTION:** Ingestion of this or other soldering products may cause headache, nausea, and muscular pain.

**INHALATION:** Inhalation of the fumes from this or other soldering products may cause headache, nausea and muscular pain.

**CARCINOGENICITY:** Not listed as a carcinogen by NTP, OSHA, or ACGIH.

**MEDICAL CONDITIONS AGGRAVATED:** Pre-existing conditions of the lungs, kidneys, nervous system and possibly reproductive systems; diseases of the blood forming organs

**ROUTES OF ENTRY:** Inhalation, ingestion, eye or skin contact.

### 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt. %	CAS
Tin	85.3 - 86.3	7440-31-5
Silver	2.4 - 2.8	7440-22-4
Copper	0.2 - 0.6	7440-50-8
Terpene Alcohol	< 2	98-55-5
Polyethylene Glycol	< 1	25322-68-3
Surfactant	< 2	102-60-3

### 4. FIRST AID MEASURES

**EYES: MOLTEN PRODUCT:** Cool burns with plenty of low-pressure water. Get immediate medical attention. **SOLID PRODUCT:** Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Get medical attention if irritation develops.

**SKIN: MOLTEN PRODUCT:** Immediately cool skin burns with water and cold packs for at least 15 minutes. Do not put ice directly on the skin. Do not attempt to remove solidified product from the skin, as damage may result. Get immediate medical attention. **SOLID PRODUCT:** Immediately wash skin with soap and copious amounts of water. Use lotion to prevent dryness. Get medical attention if irritation develops.

**INGESTION:** If person is conscious, immediately give 2 glasses of water. Do not induce vomiting. Get immediate medical attention.

# SAFETY DATA SHEET



Date Issued : 05/13/2022

SDS No : 769LF

Date Revised : 07/26/2022

Revision No : 3

## Delta Lead Free Water Soluble Solder Paste Type 769LF

**INHALATION:** If symptoms of overexposure are experienced, evacuate to fresh air. If symptoms persist, seek medical attention.

### SIGNS AND SYMPTOMS OF OVEREXPOSURE

**SKIN:** Discomfort or rash.

**INHALATION:** Irritation of the pulmonary system.

**CHRONIC EFFECTS:** Prolonged or repeated exposure due to ingestion may cause anemia, insomnia, weakness, constipation and abdominal pain. Prolonged or repeated exposure due to skin exposure and inhalation may cause skin rash and damage to the mucous membranes.

**COMMENTS:** If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this SDS to the physician/health care professional.

### 5. FIRE FIGHTING MEASURES

**EXPLOSION HAZARDS:** None known.

**FIRE FIGHTING EQUIPMENT:** Self contained breathing apparatus with full face piece operated in positive pressure demand mode, appropriate turn-out gear and chemical resistant personal protective equipment is recommended.

### 6. ACCIDENTAL RELEASE MEASURES

**GENERAL PROCEDURES:** Scoop up material and deposit in appropriate containers. Clean up residual spill area with isopropanol or detergent water.

**RELEASE NOTES:** Avoid repeated or prolonged breathing or skin contact. Wash hands immediately, and remove material from under the fingernails.

### 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Do not store or use near sparks or open flames. Keep containers tightly closed and upright when not in use in order to prevent leakage.

### 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

# SAFETY DATA SHEET



Date Issued : 05/13/2022  
 SDS No : 769LF  
 Date Revised : 07/26/2022  
 Revision No : 3

## Delta Lead Free Water Soluble Solder Paste Type 769LF

### EXPOSURE GUIDELINES

OSHA HAZARDOUS COMPONENTS (29 CFR1910.1200)				
EXPOSURE LIMITS				
Chemical Name	Type		ppm	mg/m <sup>3</sup>
Tin	OSHA PEL	TWA	NL ppm <sup>[1]</sup>	2.00 mg/m <sup>3</sup> <sup>[1]</sup>
		STEL	NL ppm	NL mg/m <sup>3</sup>
	ACGIH TLV	TWA	NL ppm	2.00 mg/m <sup>3</sup>
		STEL	NL ppm	NL mg/m <sup>3</sup>
	Supplier OEL	TWA	NL ppm	NL mg/m <sup>3</sup>
		STEL	NL ppm	NL mg/m <sup>3</sup>
Silver	OSHA PEL	TWA	NL ppm <sup>[1]</sup>	0.10 mg/m <sup>3</sup> <sup>[1]</sup>
		STEL	NL ppm	NL mg/m <sup>3</sup>
	ACGIH TLV	TWA	NL ppm	0.10 mg/m <sup>3</sup>
		STEL	NL ppm	NL mg/m <sup>3</sup>
	Supplier OEL	TWA	NL ppm	NL mg/m <sup>3</sup>
		STEL	NL ppm	NL mg/m <sup>3</sup>
Copper	OSHA PEL	TWA	NL ppm <sup>[1]</sup>	0.20 mg/m <sup>3</sup> <sup>[1]</sup>
		STEL	NL ppm	NL mg/m <sup>3</sup>
	ACGIH TLV	TWA	NL ppm	0.20 mg/m <sup>3</sup>
		STEL	NL ppm	NL mg/m <sup>3</sup>
	Supplier OEL	TWA	NL ppm	NL mg/m <sup>3</sup>
		STEL	NL ppm	NL mg/m <sup>3</sup>

**Footnotes:**  
 1. NL = Not Listed

**ENGINEERING CONTROLS:** General (mechanical) room ventilation is expected to be satisfactory where this product is stored and handled and in closed equipment. Special local ventilation is needed at points where vapors can be expected to escape into the workplace air.

### PERSONAL PROTECTIVE EQUIPMENT

**EYES AND FACE:** Face shield, safety glasses with side shield or chemical splash goggles. When working with

# SAFETY DATA SHEET



**Date Issued :** 05/13/2022  
**SDS No :** 769LF  
**Date Revised :** 07/26/2022  
**Revision No :** 3

## Delta Lead Free Water Soluble Solder Paste Type 769LF

molten material, face shield is recommended.

**SKIN:** Rubber, chemical resistant gloves. When material is heated, wear gloves to protect against thermal burns.

**RESPIRATORY:** Not normally needed in well ventilated areas. If the ventilation is insufficient to remove smoke from soldering processes, use NIOSH/MSHA approved cartridge type respirator.

**PROTECTIVE CLOTHING:** Protective clothing and safety shoes as necessary to minimize contact.

**WORK HYGIENIC PRACTICES:** Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

**OTHER USE PRECAUTIONS:** Eye wash station and quick drench safety shower in immediate work area.

### 9. PHYSICAL AND CHEMICAL PROPERTIES

**ODOR:** Mild

**APPEARANCE:** Paste

**COLOR:** Metallic gray

**FLASH POINT AND METHOD:** > 204°C (400°F)

**LOWER EXPLOSION LIMIT:** Not Established

**AUTOIGNITION TEMPERATURE:** > 227°C (440°F)

**VAPOR PRESSURE:** Not Determined

**VAPOR DENSITY:** Not Determined

**BOILING POINT:** 300°C (572°F) (vehicle)

**MELTING POINT:** 217°C (422°F) to 219°C (426°F)

**SOLUBILITY IN WATER:** Partially Soluble

**SPECIFIC GRAVITY:** 7.31 to 7.47 (water=1)

### 10. STABILITY AND REACTIVITY

**HAZARDOUS POLYMERIZATION:** Will not occur under normal use and storage conditions.

**STABILITY:** Stable under ordinary use and storage conditions.

**HAZARDOUS DECOMPOSITION PRODUCTS:** May emit toxic fumes of carbon monoxide and carbon dioxide.

**INCOMPATIBLE MATERIALS:** Strong acids and strong oxidizers should be avoided..

### 11. TOXICOLOGICAL INFORMATION

### 12. ECOLOGICAL INFORMATION

**GENERAL COMMENTS:** No information on ecological toxicity or biodegradability is available at this time.

### 13. DISPOSAL CONSIDERATIONS

# SAFETY DATA SHEET



**Date Issued :** 05/13/2022  
**SDS No :** 769LF  
**Date Revised :** 07/26/2022  
**Revision No :** 3

## Delta Lead Free Water Soluble Solder Paste Type 769LF

**DISPOSAL METHOD:** Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

### 14. TRANSPORT INFORMATION

**DOT (DEPARTMENT OF TRANSPORTATION)**

**PROPER SHIPPING NAME:** Not regulated by DOT

### 15. REGULATORY INFORMATION

**UNITED STATES**

**SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)**

**311/312 HEALTH HAZARDS:** Chronic health hazard.

**313 REPORTABLE INGREDIENTS:** Silver CAS# 7440-22-4, Copper CAS# 7440-50-8 (weight percentages can be determined from product label)

**EPCRA SECTION 313 SUPPLIER NOTIFICATION**

Chemical Name	Wt. %	CAS
Copper	0.2 - 0.6	7440-50-8

**TSCA (TOXIC SUBSTANCE CONTROL ACT)**

Chemical Name	CAS
Copper	7440-50-8

**TSCA STATUS:** All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances Control Act (TSCA) Chemical Substance Inventory.

### 16. OTHER INFORMATION

**APPROVED BY:** P. Han    **TITLE:** Technical Director

**Date Revised:** 07/26/2022

**INFORMATION CONTACT:** (630) 628-8083

**REVISION SUMMARY:** This SDS replaces the 07/26/2022 SDS. Revised: **Section 2: GHS LABEL, PRECAUTIONARY STATEMENT(S).**

# SAFETY DATA SHEET



**Date Issued :** 05/13/2022

**SDS No :** 769LF

**Date Revised :** 07/26/2022

**Revision No :** 3

## Delta Lead Free Water Soluble Solder Paste Type 769LF

### HMIS RATING

<b>HEALTH</b>	<input type="checkbox"/>	<b>1</b>
<b>FLAMMABILITY</b>		<b>1</b>
<b>PHYSICAL HAZARD</b>		<b>0</b>
<b>PERSONAL PROTECTION</b>		<b>B</b>

**MANUFACTURER DISCLAIMER:** The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Safety Data Sheets as a source of hazards information and response.