

Date Issued : 01/01/2007 SDS No : PF400 Date Revised : 05/20/2022 Revision No : 6

# Qualitek® R.A. Paste Flux PF400

# 1. PRODUCT AND COMPANY IDENTIFICATION

**PRODUCT NAME:** Qualitek® R.A. Paste Flux PF400 **PRODUCT DESCRIPTION:** Paste Flux

# MANUFACTURER

Qualitek International, Inc. 315 Fairbank St. Addison, IL 60101 Emergency Phone: (800) 535-5053 Customer Service: (630) 628-8083

# 24 HR. EMERGENCY TELEPHONE NUMBERS

1-800-535-5053 Infotrac 1-352-323-3500 Outside the U.S.

## 2. HAZARDS IDENTIFICATION

## **GHS CLASSIFICATIONS**

Health:

Eye Irritation, Category 2A

## **GHS LABEL**



## SIGNAL WORD: WARNING

## HAZARD STATEMENTS

H319: Causes serious eye irritation.

## PRECAUTIONARY STATEMENT(S)

#### **Prevention:**

P280: Wear protective gloves/protective clothing/eye protection/face protection. P264: Wash hands thoroughly after handling.

#### **Response:**

P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P337+P313: If eye irritation persists: Get medical advice/attention.

#### **Disposal:**

P501: Dispose of contents/container in accordance to local/regional/national/international regulations.

# POTENTIAL HEALTH EFFECTS

EYES: Fumes from this and other soldering products may cause eye irritation.



# Qualitek® R.A. Paste Flux PF400

SKIN: Vapors from this and other soldering products may cause skin irritation.

**INGESTION:** Ingestion of this or other soldering products may cause headache, nausea, and muscular pain.

**INHALATION:** Inhalation of the fumes from this or other soldering products may cause headache, nausea and muscular pain.

# 3. COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	Wt.%	CAS
Modified Rosin	< 60	65997-05-9
Glycol Ether DB	< 20	112-34-5

# 4. FIRST AID MEASURES

**EYES:** MOLTEN PRODUCT: Cool burns with plenty of low-pressure water. Get immediate medical attention. SOLID PRODUCT: Remove any contact lenses. Immediately flush eyes with large quantities of water for at least 15 minutes. Get medical attention if irritation develops.

**SKIN:** MOLTEN PRODUCT: Immediately cool skin burns with water and cold packs for at least 15 minutes. Do not put ice directly on the skin. Do not attempt to remove solidified product from the skin, as damage may result. Get immediate medical attention. SOLID PRODUCT: Immediately wash skin with soap and copious amounts of water. Use lotion to prevent dryness. Get medical attention if irritation develops.

**INGESTION:** If victim is conscious, give several glasses of water and keep the airway clean. Get medical attention.

**INHALATION:** Move person to fresh air. If breathing is stopped or is labored, give assisted respiration (e.g. mouth-to-mouth). Supplemental oxygen may be used. Get medical attention.

# SIGNS AND SYMPTOMS OF OVEREXPOSURE

**CHRONIC EFFECTS:** Prolonged or repeated exposure due to ingestion may cause anemia, insomnia, weakness, constipation and abdominal pain. Prolonged or repeated exposure due to skin exposure and inhalation may cause skin rash and damage to the mucous membranes.

**COMMENTS:** If victims of chemical over-exposure are taken for medical attention, give a copy of the label or this SDS to the physician/health care professional.

# 5. FIRE FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Carbon dioxide, dry chemical or appropriate foam. Water may be effective for cooling containers but not for extinguishing.

**EXPLOSION HAZARDS:** Closed containers may explode when exposed to fire conditions.

FIRE FIGHTING EQUIPMENT: Self contained breathing apparatus and full protective turn-out gear.

# 6. ACCIDENTAL RELEASE MEASURES

**GENERAL PROCEDURES:** Scoop up material and deposit in appropriate containers. Clean up residual spill area with isopropanol or detergent water.



# Qualitek® R.A. Paste Flux PF400

# 7. HANDLING AND STORAGE

**GENERAL PROCEDURES:** Store in a cool dry place away from incompatible materials. Keep away from heat, flame, sparks and other sources of ignition. Keep containers closed when not in use.

# 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

**ENGINEERING CONTROLS:** Local exhaust may be necessary if working with the product in enclosed areas or at elevated temperatures.

# PERSONAL PROTECTIVE EQUIPMENT

EYES AND FACE: Face shield, safety glasses with side shield or chemical splash goggles.

SKIN: Rubber, chemical resistant gloves. When material is heated, wear gloves to protect against thermal burns.

**RESPIRATORY:** Not normally needed in well ventilated areas. If the ventilation is insufficient to remove smoke from soldering processes, use NIOSH/MSHA approved cartridge type respirator.

PROTECTIVE CLOTHING: Protective clothing and safety shoes as necessary to minimize contact.

**WORK HYGIENIC PRACTICES:** Good personal hygiene practices should be used. Wash after any contact, before eating, and at the end of the work period.

OTHER USE PRECAUTIONS: Eye wash station and quick drench safety shower in immediate work area.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

## **ODOR:** Mild

**APPEARANCE:** Smooth amber paste.

**PERCENT VOLATILE:** 17 at 100°C (212°F)

**FLASH POINT AND METHOD:** > 116°C (240°F)

LOWER EXPLOSION LIMIT: N/E

**AUTOIGNITION TEMPERATURE: >** 227°C (440°F)

VAPOR PRESSURE: Not Determined

VAPOR DENSITY: Not Determined

BOILING POINT: 256°C (493°F) @ 760 mmHg

**MELTING POINT:** > 100°C (212°F)

SOLUBILITY IN WATER: Partially Soluble

## **10. STABILITY AND REACTIVITY**

# HAZARDOUS POLYMERIZATION: Will not occur.

**STABILITY:** Stable under ordinary use and storage conditions.

**HAZARDOUS DECOMPOSITION PRODUCTS:** Under fire conditions carbon dioxide and carbon monoxide may be evolved.



# Qualitek® R.A. Paste Flux PF400

INCOMPATIBLE MATERIALS: Strong acids and strong oxidizers should be avoided..

# **11. TOXICOLOGICAL INFORMATION**

# CARCINOGENICITY

**IARC:** Not listed.

**NTP:** Not listed.

**OSHA:** Not listed.

## **12. ECOLOGICAL INFORMATION**

GENERAL COMMENTS: No information on ecological toxicity or biodegradability is available at this time.

## **13. DISPOSAL CONSIDERATIONS**

**DISPOSAL METHOD:** Dispose of this material, contaminated absorbent material and other contaminated materials in an approved waste disposal facility, according to all applicable Federal, State, and Local regulations. Recovery and reuse, rather than disposal, should be the ultimate goal in handling efforts.

## **14. TRANSPORT INFORMATION**

## DOT (DEPARTMENT OF TRANSPORTATION)

PROPER SHIPPING NAME: Not regulated by DOT

AIR (ICAO/IATA)

SHIPPING NAME: Not regulated

## **VESSEL (IMO/IMDG)**

SHIPPING NAME: Not regulated

## CANADA TRANSPORT OF DANGEROUS GOODS

SHIPPING NAME: Not regulated

## **15. REGULATORY INFORMATION**

## **UNITED STATES**

## SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT)

311/312 HEALTH HAZARDS: Not considered a hazard.

## 313 REPORTABLE INGREDIENTS: None.

## TSCA (TOXIC SUBSTANCE CONTROL ACT)

Chemical Name	CAS	TSCA SECTION
Glycol Ether DB	112-34-5	12b,

TSCA STATUS: All ingredients are listed or are exempt from listing (as polymers) on the Toxic Substances



Date Issued : 01/01/2007 SDS No : PF400 Date Revised : 05/20/2022 Revision No : 6

# Qualitek® R.A. Paste Flux PF400

Control Act (TSCA) Chemical Substance Inventory.

**CALIFORNIA PROPOSITION 65:** When used for soldering and similar applications chemicals may be produced which are known to some states to cause birth defects or other reproductive harm.

# **16. OTHER INFORMATION**

**REASON FOR ISSUE:** Renewal date updated due to expiration.

APPROVED BY: P. Han TITLE: Technical Director

PREPARED BY: J. Saleda-Layton Date Revised: 05/20/2022

INFORMATION CONTACT: (630) 628-8083

**REVISION SUMMARY:** This SDS replaces the 05/22/2019 SDS. Revised: **Section 2:** GHS CLASSIFICATIONS, GHS LABEL, PRECAUTIONARY STATEMENT(S).



**MANUFACTURER DISCLAIMER:** The information contained herein is based upon data considered to be accurate and is offered solely for information, customer consideration and investigation. The manufacturer extends no warranties, makes no representations and assumes no responsibility as to the accuracy, completeness or suitability of this data for any purchaser's use. The content of this Safety Data Sheet relates only to this product as sold and does not relate to use with any other material or in any process. All chemical products should be used only by, or under, the direction of technically qualified personnel, who are aware of the hazards involved and of the necessity for reasonable care in handling. Hazard communication regulations, United States Occupational Health and Safety (OSHA) and Canadian Workplace Hazardous Materials Information System (WHMIS) require that employees must be trained in the use of Safety Data Sheets as a source of hazards information and response.